

All dimensions shown are in millimetres

All steel construction: **dia 25mm x 1.8mm tubes**

Connections: **1.2m long flying lead (3 core)**

Immersion heater rating: **IPX4 or better**

Manufactured for Bisque in Italy

Model	Output Watts	Weight kg	Height ± 2mm	Length ± 2mm	Fixing Centres ± 2mm
AR/E 120-50	200	8	1240	525	1140

Tools & Material Required

- Tape measure
- Screwdriver - large flathead
- Electric drill
- Masonry drill bit
- Spirit level
- Stepladder (for taller radiators)

Key	Component	Qty
A	Wall Plug	3
B	Bracket	3
C	Screw, 7mm dia x 70mm	3
D	Grub Screw	6
E	Allen Key - 3mm	1




fig 1. Bracket Positions

Assembly Instructions

Accurately mark out bracket holes on wall using spirit level, to dimensions as shown on Technical Data Sheet.

Depending on radiator height, drill three holes to a minimum depth of 65mm & insert wall plugs (A).

Attach brackets (B) to wall with screws (C).

Position brackets (B) on wall with grub screw holes as shown in figure 1 for maximum rigidity before tightening screws (C).

Hang radiator onto brackets (B) by inserting lugs into brackets (B).

Tighten grub screws (D) with Allen key (E).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

